

# Cooling Incubator(LCD)

## Microprocessor controller (with timing function)

### Features:

- Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable.
- Large LCD screen
- Latest PID controller
- R134a refrigerant, imported compressor
- Independent temperature-limiting alarm system ensures experiments run safely. (option)
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature.(option)
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement.



## Specifications

Model	Cooling Incubator			Cooling Incubator (with UV light)		
				CB - 70	CB - 150	CB - 250
Temperature Range	0~60℃					
Display Resolution	0.1℃					
Temperature Stability	HIGH ±0.3℃ LOW ±0.5℃					
Electrical Requirement	220V 50HZ					
Ambient Temperature	+5~35℃					
Power consumption	400W	700W	900W	400W	700W	900W
Interior Dimension (WxDxH)mm	400×440×500	500×460×800	520×550×1050	400×440×500	500×460×800	520×550×1050
Shelves	2(pcs)	3(pcs)	3(pcs)	2(pcs)	3(pcs)	3(pcs)
Timing Range	1~9999min					

## Options:

- Intelligent programmable temperature & Humidity controller



- Printer



- Independent temperature-limiting Alarm system



- BOD socket



- RS485 connector



- UV Sterilizer Syatom

